

A1. Wiring Ducts

## EASCO® FD Type Flexible Wiring Duct (FD型拨开式线槽)



Materials: Flexible Polypropylene.

Feature:

- UL Recognized continuous use temperature: 149°F(65°C).
- They offer good insulation properties and are resistant to chemicals, making them suitable for a wide range of applications.
- UL 94 flammability rating of V-2 or V-0.
- Factory applied adhesive tape provided for easy mounting.

Standard Length: 500MM


Color: White(RAL9003), Gray(RAL7042), Black.



WxH

- G = Gray
- W = White
- B = Black

Article No.	Part No.	Wd. (W)	Ht. (H)	Color	Pkg Qty (pcs)
货号	型号	宽度 (W)	高度 (H)	颜色	包装数 (根)
A0101.014.0001	FD20G(V2)	20	20	Grey(灰色)	100
A0101.014.0002	FD30G(V2)	30	30	Grey(灰色)	100
A0101.014.0003	FD40G(V2)	38	35	Grey(灰色)	100
A0101.014.0004	FD20W(V2)	20	20	White(白色)	100
A0101.014.0005	FD30W(V2)	30	30	White(白色)	100
A0101.014.0006	FD40W(V2)	38	35	White(白色)	100
A0101.014.0007	FD20B(V2)	20	20	Black(黑色)	100
A0101.014.0008	FD30B(V2)	30	30	Black(黑色)	100
A0101.014.0009	FD40B(V2)	38	35	Black(黑色)	100
A0101.014.0010	FD20G(V0)	20	20	Grey(灰色)	100
A0101.014.0011	FD30G(V0)	30	30	Grey(灰色)	100
A0101.014.0012	FD40G(V0)	38	35	Grey(灰色)	100
A0101.014.0013	FD20W(V0)	20	20	White(白色)	100
A0101.014.0014	FD30W(V0)	30	30	White(白色)	100
A0101.014.0015	FD40W(V0)	38	35	White(白色)	100
A0101.014.0016	FD20B(V0)	20	20	Black(黑色)	100
A0101.014.0017	FD30B(V0)	30	30	Black(黑色)	100
A0101.014.0018	FD40B(V0)	38	35	Black(黑色)	100



A2. Cable Ties

A3. Din Rails

A4. Cable Markers

A5. Cable Clamps

A6. Wrapping Bands

A7. Nylon Cable Gland

A8. Metal Cable Gland

A9. Plastic Flexible Conduit

A10. Metal Flexible Conduit

A11. Terminal

A12. Copper Tube Terminals

A13. Heat Shrinkable Tubings

A14. Bus Bar Insulators

A15. Tool

A16. Cable Clip

A17. Insulating Nut

A18. Nylon Cable Carrier

## EASCO® FA Type Flexible Wiring Duct (FA型拨开式线槽)

Materials: Flexible Polypropylene.

Feature:

- UL Recognized continuous use temperature: 149°F(65°C).
- They offer good insulation properties and are resistant to chemicals, making them suitable for a wide range of applications.
- UL 94 flammability rating of V-0.
- Factory applied adhesive tape provided for easy mounting.


Standard Length: 500MM

Color: Gray(RAL7042).



- G = Gray

Article No.	Part No.	Wd. (W)	Ht. (H)	Color	Pkg Qty (pcs)
货号	型号	宽度 (W)	高度 (H)	颜色	包装数 (根)
A0101.015.0001	FA25G(V0)	12.5	19	Grey(灰色)	100
A0101.015.0002	FA35G(V0)	25.4	35	Grey(灰色)	100



WxH

